

SAFETY DATA SHEET

Tech B Compound



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Tech B Compound
Product code : 858BEL,859BEL
Product description : filler
Product type : Solid.
Other means of identification : Not available.
Trade name : Tech B Compound

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Other non-specified industry: Rubber Filler

1.3 Details of the supplier of the safety data sheet

Distributor : Tech Europe 15 Ballinderry Road, Lisburn, BT28 2SA, UK, info@techeurope.co.uk, Chemtrec UK - +(44)-870-8200418
Manufacturer : Tech International, 200 East Coshocton Street, Johnstown, Ohio 43031, 740-967-9015 CHEMTREC: 1-800-424-9300
e-mail address of person responsible for this SDS : jsellers@techtirerepairs.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : CHEMTREC DE: 0800-181-7059
 CHEMTREC Netherlands: +(31)-858880596
 CHEMTREC Poland (Warsaw): +(48)-223988029

Supplier

Telephone number : +44 2892 665721
Hours of operation : 09.00-17.00 GMT
Information limitations : Material Safety Data Sheet

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Repr. Cat. 3; R63
 Xn; R48/20
 Xi; R38
 R67

Human health hazards : Possible risk of harm to the unborn child. Also harmful: danger of serious damage to health by prolonged exposure through inhalation. Irritating to skin. Vapors may cause drowsiness and dizziness.

Date of issue/Date of revision : 11/12/2014.

1/15

SECTION 2: Hazards identification

Environmental hazards : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

2.2.1 Label elements

Hazard pictograms :



Signal word :

Warning

Hazard statements :

Harmful if swallowed.
 Causes serious eye irritation.
 Causes skin irritation.
 Suspected of damaging the unborn child.
 May cause drowsiness and dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 Very toxic to aquatic life.
 Toxic to aquatic life with long lasting effects.

Precautionary statements

General :

Not applicable.

Prevention :

Obtain special instructions before use. Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Do not breathe dust.

Response :

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

Storage :

Store locked up.

Disposal :

Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.2.2 Label elements

Hazard symbol or symbols :



Indication of danger :

Toxic, Dangerous for the environment

Risk phrases :

R63- Possible risk of harm to the unborn child.
 R48/20- Also harmful: danger of serious damage to health by prolonged exposure through inhalation.
 R38- Irritating to skin.
 R67- Vapors may cause drowsiness and dizziness.

Safety phrases :

S53- Avoid exposure - obtain special instructions before use.
 S36/37- Wear suitable protective clothing and gloves.
 S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

Hazardous ingredients :

toluene
 Distillates (petroleum), solvent-dewaxed heavy paraffinic
 Distillates (petroleum), hydrotreated heavy paraffinic

Supplemental label elements :

Not applicable.

Special packaging requirements

Tech B Compound

SECTION 2: Hazards identification

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	25-35	F; R11 Repr. Cat. 3; R63 Xn; R48/20, R65 Xi; R38 R67	Flam. Liq. 2, H225 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	[1] [2]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	0.1-1	-	-	[1] [2]
Distillates (petroleum), hydrotreated heavy paraffinic	EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	0.1-1	-	-	[1] [2]
			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H-statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 11/12/2014.

3/15

SECTION 3: Composition/information on ingredients

Note L: This component has been tested by Supplier. According to Supplier, the component complies with the criteria of Note L in Annex I of 67/548/EEC, and is exempt from a classification of T; R45. (Contains less than 3% DMSO) See "Section 11: Toxicological Information" for information regarding the classification of substances. The classification for aspiration hazards (R65), does not apply for products placed on the market in aerosol containers. (EU-Directive 67/548 Annex VI 9.4)

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Get medical attention immediately. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Vapors may cause drowsiness and dizziness.
- Skin contact** : Irritating to skin.
- Ingestion** : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : No specific data.

SECTION 4: First aid measures

- Inhalation** : Adverse symptoms may include the following:
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
 irritation
 redness
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : No specific fire or explosion hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
 carbon dioxide
 carbon monoxide
 sulfur oxides
 metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

- Small spill** : Move containers from spill area. Avoid dust generation. Place spilled material in a designated, labeled waste container. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- 7.2 Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Tech B Compound

SECTION 7: Handling and storage

7.3 Specific end use(s)

- Recommendations** : Not available.
Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
toluene	ACGIH TLV (United States, 3/2012). TWA: 20 ppm 8 hours.
zinc oxide	ACGIH TLV (United States, 3/2012). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction STEL: 10 mg/m ³ 15 minutes. Form: Respirable fraction
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ACGIH TLV (United States, 3/2012). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 3/2012). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived effect levels

No DELs available.

Predicted effect concentrations

No PECs available.

8.2 Exposure controls

- Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Date of issue/Date of revision : 11/12/2014.

7/15

SECTION 8: Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

- Physical state** : Solid. [Viscous mass.]
- Color** : Black.
- Odor** : Solvent. [Strong]
- Odor threshold** : Not applicable.
- pH** : Not applicable.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : 111.1°C
- Flash point** : Closed cup: 7°C
- Evaporation rate** : 2.24 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.
- Burning time** : 188.3 s
- Burning rate** : 1.06 mm/s
- Upper/lower flammability or explosive limits** : Lower: 1.1%
Upper: 7.1%
- Vapor pressure** : 2.9 kPa [room temperature]
- Vapor density** : 3.14 [Air = 1]
- Relative density** : 1.03
- Solubility(ies)** : Not available.

Tech B Compound

SECTION 9: Physical and chemical properties

Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: 422°C
Decomposition temperature	: Not available.
Viscosity	: Dynamic (room temperature): Not applicable. Kinematic (room temperature): Not applicable.
VOC content	: 2.9 lbs/gal (347.5 g/l)
Explosive properties	: Not available.
Oxidizing properties	: Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LD50 Oral	Rat	636 mg/kg	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Conclusion/Summary : Not available.

Route	ATE value

Irritation/Corrosion

Date of issue/Date of revision : 11/12/2014.

9/15

Tech B Compound

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes	-
	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Eyes - Severe irritant	Rabbit	-	870 Micrograms	-
	Skin - Mild irritant	Pig	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 250 microliters	-
	Skin - Moderate irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
zinc oxide	Eyes - Mild irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-

Conclusion/Summary : Not available.

Sensitization

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Vapors may cause drowsiness and dizziness.

Skin contact : Irritating to skin.

Ingestion : Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Date of issue/Date of revision : 11/12/2014.

10/15

Tech B Compound

SECTION 11: Toxicological information

- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : May cause birth defects, based on animal data.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
toluene	Acute EC50 433 ppm Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 500000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
zinc oxide	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute EC50 0.042 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential	72 hours

Date of issue/Date of revision : 11/12/2014.

11/15

Tech B Compound

SECTION 12: Ecological information

	Acute LC50 98 µg/l Fresh water	growth phase Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 1.1 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
toluene	2.69	8.317637711	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 11/12/2014.

12/15

Tech B Compound

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorization](#)

[Substances of very high concern](#)

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users.

[Other EU regulations](#)

Europe inventory : Not determined.

Black List Chemicals : Not listed

Priority List Chemicals : Listed

Integrated pollution prevention and control list (IPPC) - Air : Not listed

Integrated pollution prevention and control list (IPPC) - Air

Integrated pollution prevention and control list (IPPC) - Water : Not listed

Integrated pollution prevention and control list (IPPC) - Water

Date of issue/Date of revision : 11/12/2014.

13/15

Tech B Compound

SECTION 15: Regulatory information

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
toluene	-	-	Repr. Cat. 3; R63	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	-	-	-	-
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	-	-

Chemical Weapons Convention List Schedule I Chemicals : Not listed

Chemical Weapons Convention List Schedule II Chemicals : Not listed

Chemical Weapons Convention List Schedule III Chemicals : Not listed

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

☑ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302
 Skin Irrit. 2, H315
 Eye Irrit. 2, H319
 Repr. 2, H361d
 STOT SE 3, H336
 STOT RE 2, H373

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Calculation method
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Repr. 2, H361d	Calculation method
STOT SE 3, H336	Calculation method
STOT RE 2, H373	Calculation method

Date of issue/Date of revision : 11/12/2014.

14/15

SECTION 16: Other information

Full text of abbreviated H statements	: H225 Highly flammable liquid and vapor. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness and dizziness. H350 May cause cancer. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	: Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4 Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 2, H225 FLAMMABLE LIQUIDS - Category 2 Repr. 2, H361d TOXIC TO REPRODUCTION [Unborn child] - Category 2 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 STOT RE 2, H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3
Full text of abbreviated R phrases	: R11- Highly flammable. R63- Possible risk of harm to the unborn child. R48/20- Also harmful: danger of serious damage to health by prolonged exposure through inhalation. R65- Also harmful: may cause lung damage if swallowed. R38- Irritating to skin. R67- Vapors may cause drowsiness and dizziness.
Full text of classifications [DSD/DPD]	: F - Highly flammable Repr. Cat. 3 - Toxic to reproduction category 3 Xn - Harmful Xi - Irritant
Date of printing	: 11/12/2014.
Date of issue/ Date of revision	: 11/12/2014.
Date of previous issue	: 3/25/2014.
Version	: 0.1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.